


# ELECTRIFIED LATCH RETRACTION



**ITEM CODE: DELRK**

**ELECTRIFIED LATCH RETRACTION KIT (FIELD INSTALLABLE MOTORIZED)**



**Features:**

- Convert mechanical fire exit hardware: 1000RT, 1200SVR, 1200SVRLBR, 1320CVRMD, 1320CVRWD, 1040RTNS, 1320CVRNS and 1110MLT to an electrified latch pullback device.
- The retrofit kit will maintain all UL listings on fire exit hardware.
- “PTS” push to set technology: 5 seconds electronic adjustment for easy post installation adjustment.
- “MM4S” smart module: on board diagnostics with audible feedback for adjustment and power issues.
- Electric dogging for continuous duty, auto re-engage if push pad is pulled from dogged position.
- Field switchable to “high torque” mode.
- Optional REX (Request to Exit) can be supplied and the combo of 2 kits (DELRK-REX) will maintain UL listing.
- UL listed and examined to UL10C. UL unique file #: GWVW.R39787, suitable for fire rated up to and including 3 hours.
- Voltage range 22 to 28VDC (+/- 10%)
- Unit will shutdown when voltage exceeds 28VDC.
- Standard torque mode: Average latch retraction current 900mA, Average holding current 190mA
- High torque mode: Average latch retraction current 2 Amp, Average holding current 250mA
- Lead 8’ with VD connector.
- Always refer to installation manual for correct installation and testing & commissioning.
- Consult Durable Collection for suitable power supply.

